

# DM320

## Floor-standing loudspeaker system

### Product Summary

- If greater efficiency and bass extension are called for then the DM320 with its larger enclosure and the 3-way system comes into its own.
- Equipped with two 8in bass units in a closed box configuration and the acclaimed magnetic fluid-cooled, light-alloy domed tweeter offers an extended low frequency range with higher sensitivity.

### Technical highlights

- The use of a aluminium domed tweeter immediately distinguishes the two models. The specially created 26mm (1in) tweeter enables high power handling to cope with the heavier usage imposed on modern hi-fi systems. Frequencies in excess of 20kHz are within its range.
- Subtle changes to the cabinet such as the tweeter plate, and bevelled front edges of the cabinet, help produce a dramatically more even frequency response. The B&W tradition of attention to detail manifests itself other features, such as the reinforced low-frequency driven diaphragm, the rigid die-cast chassis, and the provision for bi-wiring or bi-amplification.



<b>Description</b>	3-way 3rd-order, closed box digital monitor system with bi-wiring/bi-amplification facility	<b>Frequency Response</b>	60Hz – 20kHz ± 2dB on reference axis
<b>Drive Units</b>	1 x 26mm high-frequency with metal dome 2 x 200mm bass/midrange with rigid die-cast chassis, reinforced polypropylene and 31mm high temperature voice coil on Kapton® former	<b>Sensitivity</b>	91dB spl(2.83V 1m)
		<b>Nominal Impedance</b>	8 ohms
		<b>Power Handling</b>	25W – 100W into 8 ohms on unclipped programme
		<b>Dimensions</b>	Height: 656mm Width: 262mm Depth: 280mm
		<b>Finish</b>	Anthracite, black ash or walnut vinyl



LISTEN AND YOU'LL SEE

