

Pure and Simple

The three-way CM9 delivers truly commanding bass with the aid of twin 165mm paper/Kevlar® cone drive units. An FST® driver, with its characteristic compression surround supporting the outer edge of the distinctive Kevlar® cone, is specially developed for outstanding midrange performance. The CM9's Nautilus™ tube-loaded aluminium dome tweeter keeps high frequencies crisp and sharp all the way up to 50kHz and beyond.



Technical Specifications

Technical features	Nautilus™ tube loaded aluminium dome tweeter Kevlar® brand fibre cone FST midrange Flowport™
Description	3-way vented-box system
Drive units	1x ø25mm (1 in) aluminium dome high-frequency 1x ø150mm (6 in) woven Kevlar® cone FST midrange 2x ø165mm (6.5 in) paper/Kevlar® cone bass
Frequency range	-6dB at 30Hz and 50kHz
Frequency response	56Hz - 22kHz ±3dB on reference axis
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 10° arc
Sensitivity	89dB spl (2.83V, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 90Hz - 22kHz <0.5% 120Hz - 20kHz
Nominal impedance	8Ω (minimum 3Ω)
Crossover frequency	350Hz, 4kHz
Recommended amplifier power	30W - 200W into 8Ω on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 990mm (39 in) cabinet only 1025mm (40.4 in) including plinth but not feet Width: 200mm (7.9 in) cabinet only 320mm (12.6 in) including plinth Depth: 300mm (11.8 in) cabinet only 321mm (12.6 in) inc. grille and terminals but not plinth 370mm (14.6 in) including plinth
Net weight	26.6kg (58.5 lb)
Finish	Cabinet: Real wood veneers: Wengé, Rosenut Painted finish: Gloss Black Grille: Black



Gloss black

Wengé

Rosenut

Bowers & Wilkins

B&W Group Ltd
Dale Road
Worthing West Sussex
BN11 2BH England

T +44 (0) 1903 221800
F +44 (0) 1903 221801
info@bwgroup.com
www.bowers-wilkins.com

B&W Group (UK Sales)
T +44 1903 221 500
E uksales@bwgroup.com

B&W Group North America
T +1 978 664 2870
E marketing@bwgroupusa.com

B&W Group Asia Ltd
T +852 3 472 9300
E info@bwgroup.hk

Kevlar is a registered trademark of DuPont.
Nautilus is a trademark of B&W Group Ltd.
Flowport is a trademark of B&W Group Ltd.
Copyright © B&W Group Ltd. E&OE
B&W Group Ltd reserves the right to amend details of the specification without notice in line with technical developments