

CDM™1NT

Stand-mount/Bookshelf loudspeaker system

Product Summary

- The CDM 1NT builds on the success of the CDM1 SE product, which received countless awards for sonic excellence, build quality and overall performance. The cabinet is exquisitely finished in real wood veneers, and is skillfully fashioned to produce the graceful curves and contours that actually seek to reduce resonances and enhance clarity of sound.

Technical highlights



Tweeter on top: B&W's Tweeter on top technology ensures that the sound remains focused and time-sensitive and that the stereo-image is presented with unparalleled three dimensional accuracy.



Kevlar®: B&W developed and patented the method of using Kevlar® for loudspeaker cones to reduce unwanted standing waves. DuPont originally created Kevlar® for use in bulletproof vests.



Flowport™: Golf ball aerodynamics theory points the way towards lower distortion reflex ports. Dimples improve the way the air flows over the surface of any object. In the case of reflex ports, they offer a significant improvement over simply flaring the port ends in reducing air flow turbulence at each end of the port; so you get less chuffing noise and less compression at high sound levels.



Description	2-way vented-box system	Power handling	50W - 120W into 8 ohm on unclipped programme
Drive units	1 x 25mm alloy dome high-frequency 1 x 165mm woven Kevlar® cone bass/midrange	Dimensions	Height: 393mm Width: 220mm Depth: 290mm
Frequency response	60Hz - 20kHz ± 3dB on reference axis	Finishes	Cabinet: Real wood veneers, Black Ash, Cherrywood, Red Stained Cherrywood Grilles: Black cloth
Sensitivity	88dB spl (2.83V, 1m)		
Nominal impedance	8Ω (min 4.6Ω)		



LISTEN AND YOU'LL SEE