



Bowers & Wilkins

704 S3

Technical Information

**Technical features**

Decoupled Carbon Dome tweeter
 Continuum™ cone FST™ midrange
 Decoupled midrange
 Aerofoil™ Profile bass cones
 Flowport™

Description

3-way vented-box system

Drive units

1x ø25mm (1in) Decoupled Carbon Dome high-frequency
 1x ø130mm (5in) Continuum cone FST midrange
 2x ø130mm (5in) Aerofoil profile bass

Frequency range

43Hz to 33kHz

Frequency response

(+/-3dB from reference axis)

48Hz - 28kHz

Sensitivity

(on axis at 2.83Vrms at 1m)

88dB

Harmonic distortion

2nd and 3rd harmonics (90dB, 1m on axis)
 <1% 100Hz - 22kHz
 <0.5% 300Hz - 20kHz

Nominal impedance

8Ω (minimum 3.1Ω)

Recommended amplifier power

30W - 150W into 8Ω on unclipped programme

Max. recommended cable impedance

0.1Ω

Dimensions

Height: 925mm (36.4in) cabinet only
 964mm (38in) including tweeter and plinth

Width: 165mm (6.5in) cabinet only
 252mm (9.9in) including plinth

Depth: 263mm (10.4in) cabinet only
 300mm (11.8in) including grille and terminals
 321mm (12.6in) including plinth

Net weight

20.5kg (45.3lbs)

Finishes

Cabinet: Gloss black
 Satin white
 Mocha
 Rosenuit (APAC only)

Grille: Black
 Grey (Satin White only)